



Product Information

GP-10(0.65) SILICONE FLUID

Genesee Polymers' *GP-10(0.65) SILICONE FLUID* is a dimethyl polysiloxane that is an inert, clear and colorless liquid with a viscosity of 0.65 cPs at 25° C. Chemical inertness, non-corrosivity, thermal stability, low levels of toxicity and high lubricity make GP-10(0.65) the product of choice for many diverse applications.

GP-10(0.65) SILICONE FLUID is among the most versatile, cost-effective material for release agent, lubricant and polish applications.

TYPICAL PROPERTIES	
Appearance	Clear, Colorless Liquid
Weight/Gallon	6.0 lbs.
Viscosity	0.65 cPs
Flash Point (P.M.C.C.)	26° F
Refractive Index	1.3791
Specific Gravity	0.76

INNOVATIVE POLYMER TECHNOLOGY

APPLICATIONS

Car Polishes
Release Agents
Textile Lubricant
Vinyl Fabric Protectant
Cosmetic Applications
Internal Lubricant
Rubber and Plastic Lubricant
Defoamers

SPECIAL FEATURES

Chemical Inertness
Non-Toxic
Versatile Release Agent

PROCESSING AND SAFETY GUIDELINES

Genesee Polymers' *GP-10(0.65) Silicone Fluid* should be handled with care. Use proper precautions for handling Flammable Materials. Consult Safety Data Sheet for additional details.

PACKAGING/HANDLING/STORAGE

GP-10(0.65) Silicone Fluid is supplied in 5-gallon (30 lbs.) pails and 55-gallon (331 lbs.) drums.

GP-10(0.65) is Flammable. Keep away from open flames or welding torches, even when empty. Moisture Sensitive - maintain under nitrogen.



www.gpcsilicones.com

This information is based on tests believed to be reliable. It is given only for your information and no warranty, express or implied, is made as we cannot guarantee the test conditions not under our direct control. This data is not intended as authorization or recommendation to practice a patented invention without knowledge or permission of the patent owner.