




Product Information

GP-115 3-AMINOPROPYLMETHYLDIETHOXYSILANE

Genesee Polymers' *GP-115 3-AMINOPROPYLMETHYLDIETHOXYSILANE* is an intermediate useful for synthesis of silicone fluids with aminopropyl functionality. *GP-115* may also be used as a coupling agent for foundry resins.



TYPICAL PROPERTIES	
Appearance	Clear, Colorless Liquid
Purity	>97%
Boiling Point	85 - 88° C @ 8 mm Hg
Flash Point (P.M.C.C.)	154° F (68 °C)
Specific Gravity	0.916
Refractive Index	1.42 – 1.43

INNOVATIVE POLYMER TECHNOLOGY

PROCESSING AND SAFETY GUIDELINES

Genesee Polymers' *GP-115 3-AMINOPROPYLMETHYLDIETHOXYSILANE* should be handled with care. Use proper precautions for handling Flammable Materials. Consult Safety Data Sheet for additional details.

PACKAGING/HANDLING/STORAGE

GP-115 3-AMINOPROPYLMETHYLDIETHOXYSILANE is supplied in 5-gallon (36 lbs.) pails and 55-gallon (396 lbs.) drums.

GP-115 is Flammable. Keep away from open flames or welding torches, even when empty. Moisture Sensitive - maintain under nitrogen.



www.gpcsilicones.com

This information is based on tests believed to be reliable. It is given only for your information and no warranty, expressed or implied, is made as we cannot guarantee the test conditions not under our direct control. This data is not intended as authorization or recommendation to practice a patented invention without knowledge or permission of the patent owner.