

GP-235 DIMETHOXYDIPHENYLSILANE

Genesee Polymers' *GP-235 DIMETHOXYDIPHENYLSILANE* is an intermediate useful for synthesis of silicone fluids with high temperature stability. *GP-235* may also be used as a catalyst in the synthesis of polypropylene.

TYPICAL PROPERTIES	
Appearance	Clear, Colorless Liquid
Purity	>97%
Boiling Point	320 °F (160 °C) @ 15 mm Hg
Flash Point (P.M.C.C.)	250° F (121°C)
Specific Gravity	1.08
Refractive Index	1.5350 – 1.5450

Product Code: C-3008 Version: 3.0 Revision Date: February 18, 2019

PROCESSING AND SAFETY GUIDELINES

Genesee Polymers' *GP-235 DIMETHOXYDIPHENYLSILANE* should be handled with care. Use proper precautions for handling industrial chemicals. Consult Safety Data Sheet for additional details.

PACKAGING/HANDLING/STORAGE

GP-235 DIMETHOXYDIPHENYLSILANE is supplied in 5-gallon (40 lbs.) pails and 55-gallon (440 lbs.) drums.

Moisture Sensitive - maintain under nitrogen.



www.gpcsilicones.com

This information is based on tests believed to be reliable. It is given only for your information and no warranty, expressed or implied, is made as we cannot guarantee the test conditions not under our direct control. This data is not intended as authorization or recommendation to practice a patented invention without knowledge or permission of the patent owner.