

GP-32 SILICONE FLUID

Genesee Polymers' *GP-32 SILICONE FLUID* is an epoxy functional dimethylpolysiloxane copolymer fluid with the following structure where x = 96.5 and y = 5.5:

TYPICAL PROPERTIES	
Appearance	Clear to Slightly Hazy, Colorless to Light Straw Liquid
Weight/Gallon	8.0 lbs
Flash Point (P.M.C.C.)	>300° F
Refractive Index	1.4154
Specific Gravity	0.99
Molecular Weight	8,300 (Calculated)
Epoxy Equivalent Weight	1,515 (Calculated)
Viscosity at 25° C	270 cSt

APPLICATIONS

GP-32 SILICONE FLUID is suggested for use as a reactive silicone intermediate in the synthesis of organosilicone copolymer products.

The epoxy-alkyl functionality also provides a site for reactions with alcohol, acid and amine functional monomers, allowing the synthesis of a variety of organo-functional silicones.

PACKAGING/HANDLING/STORAGE

GP-32 SILICONE FLUID is supplied in 5-gallon (40 lbs.) pails, 55-gallon (440 lbs.) drums and 330-gallon (2640 lbs.) totes.

Moisture Sensitive. Keep container tightly sealed. Store below 100° F.



www.gpcsilicones.com

This information is based on tests believed to be reliable. It is given only for your information and no warranty, GPress or implied, is made as we cannot guarantee the test conditions not under our direct control. This data is not intended as authorization or recommendation to practice a patented invention without knowledge or permission of the patent owner.