



Product Information

GP-361 SILICONE FLUID

Genesee Polymers' *GP-361 SILICONE FLUID* is a 100% active, modified silicone copolymer, which is designed to provide lubrication between plastic and metal or rubber and metal surfaces.

The presence of ionic-alkyl groups in *GP-361* provides a high degree of affinity to metal surfaces, hence increasing lubricating and release characteristics at the metal/plastic or rubber interface.

Because *GP-361 SILICONE FLUID* is a silicone product, it exhibits excellent heat stability and will not break down or carbonize at normal operating conditions.

TYPICAL PROPERTIES	
Color	Clear, Colorless to Straw Liquid
Viscosity, 77° F	115 cP
Specific Gravity	0.97
Flash Point (P.M.C.C.)	>300° F
Weight/Gallon	8.0 lbs.

INNOVATIVE POLYMER TECHNOLOGY

APPLICATIONS
Rubber Molding
Textile Lubricant
Metal/Plastic Lubricant
Urethane Molding
Foundry Release
Epoxy Release

SPECIAL FEATURES
High Metal/Plastic Lubricity
Multiple Release of Plastic and Rubber
Excellent Thermal Stability

PROCESSING AND SAFETY GUIDELINES

The silicone polymer used in *GP-361 SILICONE FLUID* contains a dimethyl silicone structure, which can cause paint and adhesion problems, if not properly cleaned from molded parts.

GP-361 may be diluted with aliphatic or aromatic solvents when desired.

PACKAGING/HANDLING/STORAGE

GP-361 SILICONE FLUID is supplied in 5-gallon (40 lbs.) pails, 55-gallon (440 lbs.) drums and 330-gallon (2640 lbs.) totes.

Moisture Sensitive. Do not freeze. Do not store below 100° F.



www.gpcsilicones.com

This information is based on tests believed to be reliable. It is given only for your information and no warranty, express or implied, is made as we cannot guarantee the test conditions not under our direct control. This data is not intended as authorization or recommendation to practice a patented invention without knowledge or permission of the patent owner.