


# **GP-37 METHYLTRIETHOXYSILANE**

Genesee Polymers' *GP-37 METHYLTRIETHOXYSILANE* is an intermediate useful in the synthesis of silicone resins, silicone rubber and sol-gel coatings. *GP-37* is also used for preparing hydrophobic and release materials.



TYPICAL PROPERTIES	
Appearance	Clear, Colorless Liquid
Purity	>97%
Boiling Point	288° F (142°C)
Flash Point (P.M.C.C.)	86° F (30°C)
Specific Gravity	0.8948
Refractive Index	1.3832

## **INNOVATIVE POLYMER TECHNOLOGY**

#### PROCESSING AND SAFETY GUIDELINES

Genesee Polymers' *GP-37 METHYLTRIETHOXYSILANE* should be handled with care. Use proper precautions for handling Flammable Materials. Consult Safety Data Sheet for additional details.

### PACKAGING/HANDLING/STORAGE

*GP-37 METHYLTRIETHOXYSILANE* is supplied in 5-gallon (35 lbs.) pails and 55-gallon (396 lbs.) drums.

*GP-37* is Flammable. Keep away from open flames or welding torches, even when empty. Moisture Sensitive - maintain under nitrogen.



#### www.gpcsilicones.com

This information is based on tests believed to be reliable. It is given only for your information and no warranty, express or implied, is made as we cannot guarantee the test conditions not under our direct control. This data is not intended as authorization or recommendation to practice a patented invention without knowledge or permission of the patent owner.