

GP-526 3-MERCAPTOPROPYLMETHYLDIMETHOXYSILANE

Genesee Polymers' *GP-526 3-MERCAPTOPROPYLMETHYLDIMETHOXYSILANE* is an intermediate useful for synthesis of silicone fluids with mercaptopropyl functionality. These types of silicones can be used in thiol-ene UV cure systems.

TYPICAL PROPERTIES	
Appearance	Clear, Colorless Liquid
Purity	>98%
Boiling Point	96° C @ 30 mm Hg
Flash Point (P.M.C.C.)	199° F (93 °C)
Specific Gravity	1.00
Refractive Index	1.45

Product Code: C-2211 Version: 2.0 Revision Date: November 30, 2017

PROCESSING AND SAFETY GUIDELINES

Genesee Polymers' *GP-526 3-MERCAPTOPROPYLMETHYLDIMETHOXYSILANE* should be handled with care. Use proper precautions for handling industrial chemicals. Consult Safety Data Sheet for additional details.

PACKAGING/HANDLING/STORAGE

GP-526 3-MERCAPTOPROPYLMETHYLDIMETHOXYSILANE is supplied in 5-gallon (40 lbs.) pails and 55-gallon (440 lbs.) drums.

Moisture Sensitive - maintain under nitrogen.



www.gpcsilicones.com

This information is based on tests believed to be reliable. It is given only for your information and no warranty, expressed or implied, is made as we cannot guarantee the test conditions not under our direct control. This data is not intended as authorization or recommendation to practice a patented invention without knowledge or permission of the patent owner.