

GP-6 SILICONE FLUID

Genesee Polymers' *GP-6 SILICONE FLUID* is an amine functional silicone polymer with the following structure where x = 100 and y = 4:

The amine-alkyl functionality of *GP-6* provides a versatile reaction site for the synthesis of a variety of functional silicone polymers and silicone-organic copolymers.

The polar amine groups in *GP-6 SILICONE FLUID* also demonstrate high affinity for many substrates, suggesting use of *GP-6* in textile lubricants, plastic and rubber release and lubrication, and in car polish formulations.

GP-6 SILICONE FLUID is compatible with dimethyl silicone fluids, and with aliphatic, aromatic and chlorinated solvents.

Product Code: C-3121 Version: 2.0 Revision Date: November 29, 2017

TYPICAL PROPERTIES			
Appearance	Clear, Colorless to Light Straw Liquid		
Weight/Gallon	8.0 lbs.		
Flash Point (P.M.C.C.)	>200° F		
Specific Gravity	0.98		
% Active	100%		
Amine Number*	49		

^{*}Number of mls. of 0.1 Normal HCl needed to neutralize 10.0 grams of GP-6.

APF	LIC	ATI	ONS	S
ΑГГ	LIC	\sim 1 I	$\mathbf{v}_{\mathbf{i}}$	3

Internal Plastic Mold Release

Rust Inhibitor Coatings

Detergent Resistant Car Polishes

Silicone - Organic Copolymer Synthesis

SPECIAL FEATURES

High Amine-Alkyl Functionality

Stable Indefinitely in Closed Containers

Good Heat Stability

PROCESSING AND SAFETY GUIDELINES

Genesee Polymers' *GP-6 SILICONE FLUID* is an alkaline material due to its amine reactive groups. Care should be exercised in handling *GP-6* to prevent contact with skin or eyes. Wear safety glasses with side shields and rubber gloves when handling. Consult Safety Data Sheet for additional details.

PACKAGING/HANDLING/STORAGE

GP-6 SILICONE FLUID is supplied in 5-gallon (40 lbs.) pails, 55-gallon (440 lbs.) drums and 330-gallon (2640 lbs.) totes. Moisture Sensitive. Keep containers tightly sealed.



www.gpcsilicones.com

This information is based on tests believed to be reliable. It is given only for your information and no warranty, express or implied, is made as we cannot guarantee the test conditions not under our direct control. This data is not intended as authorization or recommendation to practice a patented invention without knowledge or permission of the patent owner.