



Product Information

GP-70-EO POLYMER EMULSION

Genesee Polymers' *GP-70-EO POLYMER EMULSION* is a 50% silicone solids emulsion of an organo-modified silicone polymer. The base silicone contains a combination of alkyl and alkylaryl side chains which help insure good compatibility with both organic cleaners, and with solvent-based paints and coatings.

The primary application of *GP-70-EO* is as a release agent, or release agent component in the molding or casting of articles which are to be painted or bonded in subsequent operations.

TYPICAL PROPERTIES	
Appearance	White, Opaque Liquid
Weight/Gallon	8.0 lbs.
Specific Gravity	0.97
pH	7.0
Silicone Content	50%, Weight
Emulsifier Type	Non-Ionic

INNOVATIVE POLYMER TECHNOLOGY

APPLICATIONS
Rubber and Plastic Release
Metal-Forming and Casting
Textile Lubricants

SPECIAL FEATURES
Stable Emulsion
Dilutable in Hard or Soft Water
Organic-Compatible
Good High Temperature Stability
Fine Particle Size
Good Lubricity

PROCESSING AND SAFETY GUIDELINES

As with any contaminant, it is recommended that *GP-70-EO POLYMER EMULSION* residues should be removed from surfaces prior to painting or bonding for best results. However, if removal is not complete, residue of *GP-70-EO* will not cause fisheyes, orange peel, or similar effects associated with conventional dimethyl silicones.

For safety information, refer to Safety Data Sheet.

PACKAGING/HANDLING/STORAGE

GP-70-EO POLYMER EMULSION is supplied in 5-gallon (40 lbs.) pails, 55-gallon (440 lbs.) drums and 330-gallon (2640 lbs.) totes. Do not store below 40° F or above 100° F.



www.gpcsilicones.com

This information is based on tests believed to be reliable. It is given only for your information and no warranty, express or implied, is made as we cannot guarantee the test conditions not under our direct control. This data is not intended as authorization or recommendation to practice a patented invention without knowledge or permission of the patent owner.