

GP-733 TRIMETHYLETHOXY SILANE

Genesee Polymers' *GP-733 TRIMETHYLETHOXY SILANE* is an intermediate useful for blocking hydroxyl or amino groups to perform reactions on multi-functional organic compounds or polymers. It is also useful for deactivating glass surfaces used in gas chromatographic applications.

$$H_3C$$
 CH_3
 CH_3
 CH_2-O
 CH_3
 CH_3
 CH_3

TYPICAL PROPERTIES	
Appearance	Clear, Colorless Liquid
Weight/Gallon @ 68° F	6.3
Flash Point (P.M.C.C.)	23° F
Specific Gravity	0.75
Boiling Range	167 - 169° F
Vapor Pressure @ 77° F	111 mm Hg.

INNOVATIVE POLYMER TECHNOLOGY

Product Code: C-0263 Version: 3.0 Revision Date: April 6, 2018

PROCESSING AND SAFETY GUIDELINES

Genesee Polymers' *GP-733 TRIMETHYLETHOXY SILANE* should be handled with care. Although *GP-733* is not highly toxic, it has a low flash point of 23° F (making it Flammable) and a high vapor pressure at room temperature. For additional safety precautions, refer to Safety Data Sheet.

PACKAGING/HANDLING/STORAGE

GP-733 TRIMETHYLETHOXY SILANE is supplied in 5-gallon (30 lbs.) pails and 55-gallon (330 lbs.) drums.

GP-733 is Flammable. Keep away from open flames or welding torches, even when drum is empty. Moisture Sensitive. Keep containers tightly sealed.



www.gpcsilicones.com

This information is based on tests believed to be reliable. It is given only for your information and no warranty, express or implied, is made as we cannot guarantee the test conditions not under our direct control. This data is not intended as authorization or recommendation to practice a patented invention without knowledge or permission of the patent owner.